



QUALITY
MEDIA AND LAMINATING SOLUTIONS

Quality 64 TLX-P

Top-Heated Roller Laminator

- Laminate up to 62" material
- Motorized nip assembly
- Fold down front table
- Auto and foot pedal running mode
- Rear rewind for finished prints



Information provided here is based on research and is believed to be reliable as of printing date. This information does not constitute a warranty. All material should be tested by purchaser to determine final suitability. Quality will not be held responsible for customers end use of product. Quality is available for directions and advice as to proper use and application of our products.



Quality 64 TLX-P

Standard Features

- Maximum laminating width 62"
- Motorized nip assembly
- 5" diameter silicone rollers
- Top and bottom windup with clutch adjustment
- Temperature range 0-265° F
- Fold down front table
- Speed 0-20 feet/minute
- Auto and foot pedal running mode
- Heavy duty lockable casters
- Flat feed print guide
- Three emergency stops
- Photoelectric nip protection
- Top and bottom easy grip supply shafts with brake tension control

Technical Specifications

- Laminating Width.....62"
- Laminating Speed0-20 feet/minute
- Maximum Mounting Thickness.....1.5"
- Maximum Laminating Temperature265° F
- Electrical Requirement.....110V 20A
- Roller Diameter5"

Packaged for Shipment

- Weight705 lbs
- Width82"
- Depth27"
- Height58"



Control Panel from Quality 64 TLX-P